

MUNI RO LE Series

Membrane Elements for Municipal Drinking Water Plants

Engineered to treat municipal potable water at lower pressures, the MUNI RO LE series enables drinking water processes to achieve reduced operating costs. Low-pressure operations also reduce membrane compaction, which increases the efficiency of the RO system. The MUNI RO LE series includes a selection of three elements featuring two different outer covers in consideration of energy conservation and salt rejection performance.

Full-Fit* or Fiberglass

Applications vary and one design cannot best serve all requirements. The MUNI RO LE series offers the unique solution-oriented option of a 365 sq. ft. Full-Fit* membrane element or standard FRP construction. While FRP construction offers comparably higher rejection performance, the creative Full-Fit* design forms a close fit within the pressure vessel walls, thus eliminating dead spaces prone to bacterial growth and adhesion, and allowing for quick and complete cleaning. In addition to this sanitizing feature, pressure drop across the elements using Full-Fit* design is significantly less than standard FRP construction (Figure 1), which may lead to substantial energy savings.

The MUNI RO LE membrane elements are tested and certified by NSF international against NSF/ANSI Standard 61 for material requirements only.

The MUNI RO LE membrane is a low energy element following a 100% Wet Test Quality Assurance




Figure 1: High Flow Rate at Low Pressure Drop

Table 1: Element Specification

Membrane	Thin-Film Membrane (TFM*)
----------	---------------------------

Model	Average permeate flow gpd (m3/day) ^{1,2}	Average NaCl rejection ^{1,2}	Minimum NaCl rejection ^{1,2}
MUNI-RO-350-LE-WT	9,200 (34.8)	99.0 %	98.0%
MUNI-RO-365-LE-WT-FF	9,600 (36.3)	98.5 %	98.0%
MUNI-RO-400-LE-WT	10,500 (39.7)	99.0 %	98.0%

¹ Average salt rejection after 24 hours operation. Individual flow rate may vary +25%/-15%.

² Testing conditions: 500ppm NaCl solution at 115psi (792.9kPa) operating pressure, 77°F, pH 7.5 and 15% recovery.

Model	Active area ft ² (m ²)	Outer wrap	Part number
MUNI-RO-350-LE-WT	350 (32.5)	Fiberglass	1266771
MUNI-RO-365-LE-WT-FF	365 (33.9)	Full-Fit*	1266803
MUNI-RO-400-LE-WT	400 (37.2)	Fiberglass	1266802

a product of
ecomagination™



Find a contact near you by visiting www.ge.com/water and clicking on "Contact Us".

* Trademark of General Electric Company; may be registered in one or more countries.

©2009, General Electric Company. All rights reserved.




Figure 1: Element Dimensions Diagram – Female

Table 2: Dimensions and Weight

Model ¹	Dimensions, inches (cm)			Boxed
	A	B ²	C ³	Weight lbs (kg)
MUNI-RO-350-LE-WT	40.0 (101.6)	1.125 (2.86)	7.9 (20.1)	35 (16)
MUNI-RO-365-LE-WT-FF	40.0 (101.6)	1.125 (2.86)	7.9 (20.1)	35 (16)
MUNI-RO-400-LE-WT	40.0 (101.6)	1.125 (2.86)	7.9 (20.1)	35 (16)

¹These elements are bagged wet before shipping.

²Internal diameter.

³The element diameter (dimension C) is designed for optimum performance in GE Water & Process Technologies pressure vessels. Others pressure vessel dimension and tolerance may result in excessive bypass and loss of capacity.

Table 3: Operating and CIP parameters

Typical Operating Pressure	110psi (758kPa)
Typical Operating Flux	10-20GFD (15-35LMH)
Maximum Operating Pressure	400psi (2,758kPa)
Maximum Temperature	Continuous operation: 112°F (50°C) Clean-In-Place (CIP): 112°F (50°C)
Minimum Crossflow	30gpm (6.8m ³ /h)
pH Range	Continuous operation: 4.0-11.0, Clean-In-Place (CIP): 2.0-11.5
Maximum Pressure Drop	Over an element: 12psi (83kPa) Per housing: 50psi (345kPa)
Chlorine Tolerance	1,000+ ppm-hours, dechlorination recommended,
Feedwater	NTU < 1 SDI < 5
Recommended single element recovery	< 15 %